

PRODUCT DATA SHEET

Sika® backing rods

Sealants Back Up Material

DESCRIPTION

Sika® backing rods is manufactured from extruded polyethylene foam, available in rods with different diameters and lengths.

USES

Sika® backing rods is used as a back up material for cold applied Sika sealants to give the sealant the correct thickness. It also acts as a bondbreaker, permitting the most efficient joint design.

CHARACTERISTICS / ADVANTAGES

- Easy to apply
- Closed cell
- No bond to most sealants
- Compatible with cold applied sealants (polyurethane, silicones)
- Different rod diameters
- Highly flexible and compressible
- Good water resistance
- Good temperature resistance
- Odourless

PRODUCT INFORMATION

Composition	Extruded Polyethylene Foam	
Packaging	Rod diameter Ø mm	Length m'
	8	550
	10	400
	13	350
	15	300
	20	200
	25	150
	30	100
	Cartons, length depending on rod diameter.	
Appearance / Colour	Grey, White	
Shelf life	12 months from the date of manufacture if unopened	
Storage conditions	Store in dry conditions and protected from heat.	

TECHNICAL INFORMATION

Chemical resistance	Good resistance to oil, petrol and solvents.
Service temperature	-40°C to +70°C

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

When installing Sika® backing rods, be careful not to cut or puncture the surface skin.
During installation avoid excessive longitudinal stretching of the rod.
For Hot-Poured-Sealants consult our Technical Department for heat-resistant quality.
Do not use as a backer, where sealant is heated and applied at a temperature above +70°C.
Rod diameter should be approx. 25% larger than the joint width.

ECOLOGY, HEALTH AND SAFETY

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Tanzania Construction Chemicals Limited

Plot No. 135
Mbezi Industrial Area, Kinondoni
P.O Box 7079 Dar es Salaam
Tanzania
Phone: +255 699 784 926



Product Data Sheet
Sika® backing rods
April 2021, Version 01.01
02051603000000008

Sikabackingrods-en-TZ-(04-2021)-1-1.pdf

