

# PRODUCT DATA SHEET

## Sikadur®-509 TZ

### GRADED, CLEANED AND DRIED SILICA SAND

#### DESCRIPTION

Sikadur®-509 TZ is graded, cleaned, dried silica sand for broadcast, building and anti-skid flooring system.

#### USES

- Proper gradation ensuring uniform broadcast finish
- Enhances slip & abrasion resistance property
- Stabilization Infill for Artificial Turf

#### CHARACTERISTICS / ADVANTAGES

#### PRODUCT INFORMATION

Packaging	25 kg bag/Bulk delivery
Shelf life	24 months from date of production
Storage conditions	The product must be stored in closed, sealed and undamaged packaging in dry conditions at temperatures between +5°C and +30°C. The packaging must be protected from moisture.

#### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### ECOLOGY, HEALTH AND SAFETY

#### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, sub-

strates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.