

PRODUCT DATA SHEET

SikaWall®-165 Water Resistant Putty

High performance, cementitious finish skimcoat for internal and external wall

DESCRIPTION

SikaWall®-165 Water Resistant Putty is a one component cementitious fine finishing coat for skimming on wall and ceilings. It's smooth finishing and good adhesion is suitable for internal and external application.

USES

- Suitable for application on concrete surfaces, lightweight concrete slabs, precast panels, soffits, brick-walls, lightweight aerated blocks and rendered surfaces
- Suitable for both internal and external application

CHARACTERISTICS / ADVANTAGES

- Provide a good fine surface finish on walls, ceilings, etc.
- Greater durability and flexibility
- Quick drying and easy to apply
- Thickness of the plaster can be varied to minimise wastage
- Non-combustible
- Non-cracking when applied at correct thickness and properly cured
- Easy to mix – just add water
- Good adhesion
- Water Resistant

PRODUCT INFORMATION

| | |
|--------------------|---|
| Composition | Cementitious mortar |
| Packaging | 25 kg bag |
| Colour | White powder |
| Shelf life | 12 months from the date of production |
| Storage conditions | Store properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Protect from direct sunlight, rain and water. |
| Density | 1.00–1.20 kg/l |
| Maximum grain size | 0.4 mm |

TECHNICAL INFORMATION

| | | | |
|---------------------------|---------------------------|-------------------|--------------|
| Tensile adhesion strength | $\geq 0.3 \text{ N/mm}^2$ | Adhesion fracture | (EN 1015-12) |
| Mixing ratio | 9 L water per 25 kg bag | | |
| Layer thickness | 0.7–2.0 mm | | |

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Do not use SikaWall®-165 Water Resistant Putty on painted or gypsum surfaces.
- Applications of SikaWall®-165 Water Resistant Putty which are too thin can result in a chalky or dusty finish that is unsuitable for painting or subsequent applications.
- Applications of SikaWall®-165 Water Resistant Putty on very porous or dry substrates can result in a chalky or dusty finish that is unsuitable for painting or subsequent applications.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate must be sound, clean, dry and free of all contaminants e.g. dirt, oils, grease, coatings, surface treatments, etc. If in doubt, apply a test area first. Dry concrete, render or SikaWall® surfaces must be prewetted before application.

MIXING

SikaWall®-165 Water Resistant Putty must be mixed with clean water at the site using a power drill whisk. Pour the required water into a suitable container then add SikaWall®-165 Water Resistant Putty while stirring continuously until a smooth consistency is achieved. Allow mixture to stand for a few minutes. Mix again and the plaster is ready for use.

APPLICATION

SikaWall®-165 Water Resistant Putty is applied either by hand with a steel trowel or spatula. The coat is then levelled off to a smooth surface with a steel trowel. Ensure that the applied coat has hardened before application of subsequent coats.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened or cured material can only be removed mechanically.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Tanzania Construction Chemicals Limited

Plot No. 135
Mbezi Industrial Area, Kinondoni
P.O Box 7079 Dar es Salaam
Tanzania
Phone: +255 699 784 926



Product Data Sheet
SikaWall®-165 Water Resistant Putty
May 2025, Version 01.01
021820201000242000

SikaWall-165WaterResistantPutty-en-TZ-(05-2025)-1-1.pdf

